







Power Diagram



Power Diagram



Machine Dimension



model	A	B	C	D	E	F	G	H	I	K
SL-6/8/10	3435	2335	680	1590	893	1556	1827	152	1578	1780
SL-6/8/10MC	3477	2564	820	1590	893	1556	1827	202	1578	1780

SPEC.	UNIT	SL-6	SL-6MC	SL-8	SL-8MC	SL-10	SL-10MC
SWING OVER BED	mm	420	420	420	420	420	420
OVER CROSS SLIND	mm	340	340	340	340	340	340
MAX. TURNING DIA	mm	320	230	320	250	320	250
MAX. WORK LENGTH	mm	420	420	480	480	460	460
DRAW TUBE BORE	mm	45	45	52	52	75	75
CHUCK SIZE	inch	6"	6"	8"	8"	10"	10"
SPINDLE DRIVE MOTOR	KW	7.5/11	5.5/7.5	7.5/11	9/11	11/15	9/11
MAX SPINDLE SPEED	rpm	4500 (6000 opt.)	4500 (6000 opt.)	4500 (4900 opt.)	4500 (4900 opt.)	3800 (4200 opt.)	3800 (4200 opt.)
MILLING SPEED RANGE	rpm		4000		4000		4000
SPINDLE NOSE		A2-5	A2-5	A2-6	A2-6	A2-8	A2-8
THROUGH SPINDLE HOLE DIA	mm	51	51	62	62	90	90
FRONT BEARING DIA	mm	80	80	100	100	130	130
SPINDLE TAPER		1/20	1/20	1/20	1/20	1/20	1/20
X AXIS TRAVEL	mm	180	160	180	180	180	180
Z AXIS TRAVEL	mm	450	450	480	480	470	470
X AXIS MOTOR	KW	1.2	1.6	1.2	1.6	1.8	1.6
Z AXIS MOTOR	KW	1.2	1.4	1.2	3.0	1.8	3.0
X AXIS RAPID TRAVERSE	m/min	30	24	30	24	24	24
Z AXIS RAPID TRAVERSE	m/min	30	24	30	24	24	24
GUIDEWAYS		Linear	Linear	Linear	Linear	Linear	Linear
NO. OF TOOL STATIONS		8	12	10(opt. 6+6)	12	10(opt. 6+6)	12
SIZE OF EXTER. TURNING TOOL	mm	20	16	25	20	25	20
BORING BAR DIA	mm	32	32	40	32	40	32
QUILL DIA	mm	58	58	58	58	58	58
QUILL TRAVEL	mm	83	83	86	86	86	86
TAILSTOCK TRAVEL	mm	420	420	420	420	420	420
QUILL TAPER		MT#4	MT#4	MT#4	MT#4	MT#4	MT#4
ELECTRICAL POWER SUPPLY	KVA	21	21	21	25	25	25
COOLANT TANK CAPACITY	Liter	100	100	100	100	100	100
COOLANT FLOW	L/min	20	20	20	20	20	20
TOTAL HEIGHT	mm	1580	1580	1580	1580	1580	1580
FLOOR SPACE LENGTH	mm	2550	2700	2550	2700	2700	2700
FLOOR SPACE WIDTH	mm	1550	1600	1550	1600	1600	1600
NET WEIGHT	kg	3310	3350	3350	3400	3450	3500

STANDARD ACCESSORIES

- 3 jaw hydraulic chuck
- Hydraulic tailstock
- Hydraulic system
- Coolant system
- Auto lubrication system
- Heat exchanger
- Work light equipment
- Hand wheel
- Foot switch for chuck clamp
- OD tool holder
- Facing tool holder
- Boring bar holder & sleeves
- Drill sleeves
- Live center
- Morse taper Sleeve
- Tool box
- Levelling pads
- Operation & maintenance manuals

OPTIONAL ACCESSORIES

- Chip conveyor
- Chip bucket
- Transformer
- Parts catcher
- Parts conveyor
- Tool setter
- Auto Door
- Bar feeder
- Bar feeder interface (LNS system)
- CE mark
- Hoisting hook package
- Levelling kit
- Additional tool holders and sleeves

All specifications, designs and characteristics shown in this catalogue are subject to change without prior notice.
Motor specifications are based on machine with Fanuc controller.



ECOCA INDUSTRIAL CO., LTD.

401, 28TH ROAD, TAICHUNG INDUSTRIAL PARK, TAICHUNG, TAIWAN.

TEL: +886-4-23597666 FAX: +886-4-23597669 http://www.ecoca.com E-mail: biz@ecoca.com

14-08-05-024E-1000-R07

ECOCA®

—Focus on every detail—

